FORM PTO		U.S. DEPA	RTMENT OF	COMM	ERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER		
TRANSMITTAL LETTER TO THE UNITED STATES				05788.0199				
DESIGNATED/ELECTED OFFICE (DO/EO/US)					U.S. APPLICATION NO.			
CONCERNING A FILING UNDER 35.U.S.C. 371					(If known, see 37CFR1.5)			
CONCERNING MILLING CINDERSS.C.S.C. 371					10/019447			
INTERNATIONAL APPLICATION NO. INT				O.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED		
PCT/EP00/06203 July					July 3, 2000	July 1, 1999		
	TITLE OF INVENTION WAVEGUIDE SYSTEMS OR STRUCTURES OR PARTS THEREOF, CONTAINING POLYCYANATE							
					LYFUNCTIONAL CYANATES AND FLU			
APPLICANT(S) FOR DO/EO/US								
	` ,			ristian	DREYER, Norbert KEIL and Crispin ZAV	VADZKI		
Applican	ıt(s) herew	ith submit	ts to the Ur	nited St	ates Designated/Elected Office (DO/EO/US) the	e following items and other information:		
1.	X	This is a	FIRST sul	bmissio	on of items concerning a filing under 35 U.S.C 3	71.		
2.		This is a	SECOND	or SU	BSEQUENT submission of items concerning a	filing under 35 U.S.C. 371.		
3.		This is an	n express re	equest	to begin national examination procedures (35 U indicated below.			
4.	X				y the expiration of 19 months from the priority	date (Article 31).		
5.	X				l Application as filed (35 U.S.C. 371 (c)(2)).			
		a.						
		b.		has be	en communicated by the International Bureau.			
		c.		is not	required, as the application was filed with the U	nited States Receiving Office (RO/US).		
		An Engli	ish languag	ge trans	lation of the International Application as filed (	35 U.S.C. 371 (c)(2)).		
J.		a.		is attac	ched hereto.			
11 m m m m m m m m m m m m m m m m m m		b.		has be	en previously submitted under 35 U.S.C. 154 (d	)(4).		
	X	Amendm	Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)).					
		a.						
# ###		b.			een communicated by the International Bureau.			
The state of the s		c.		have n	ot been made; however, the time limit for making	ng such amendments has NOT expired.		
ini Pi		d.			ot been made and will not be made.			
T		An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).						
					he inventor(s) (35 U.S.C. 371 (c)(4)).			
ŢŢ.		An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).						
			_					
ems 11	to 20 bei	ow concei	rn docume	ent(s) o	r information included:			
	·X	Informat	ion Disclos	sure St	atement under 37 CFR 1.97 and 1.98			
An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 ar					ance with 37 CFR 3.28 and 3.31 is			
	v	included.			ndmånt			
X A FIRST preliminary amendment.								
	☐ A SECOND or SUBSEQUENT preliminary amendment.  A Substitute precification							
	<ul><li>☐ A Substitute specification.</li><li>☐ A change of power of attorney and/or address letter.</li></ul>							
	A change of power of attorney and/or address letter.  A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821-1.825.							
		_			ished international application under 35 U.S.C.			
				_	lish language translation of the international app			
	X		ms or info	-		```		
				of cover page of International Publication No. V	VO 01/02464 A1			
		b.			of Notification of Missing Requirements.			
		c.			,			

10/019447			INTERNATIONAL APPLICATION NO. PCT/EP00/06203		ATTORNEY'S DOCKET NUMBER: 05788.0199	
21.  The following fees are submitted:					CALCULATIONS PTO USE ONLY	
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):						^
Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO						
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00						
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search fee (37 CFR 1.445(a)(2)) paid to USPTO						
International preli	International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4)					
International prelin	minary exa	amination fee (37	CFR 1.482) paid to	\$100.00		
				RIATE BASIC FEE AMOUNT =	\$890.00	
months from the ea	.00 for fur arliest clai	mishing the oath o	r declaration later than (37 CFR 1.492 (e)).	□ 20 □ 30	\$	
CLAIMS		IBER FILED	NUMBER EXTRA	RATE		
Total Claims	33	- 20 =	13	x \$18.00	\$234.00	
Independent Claims	1	-3 =		x \$84.00	\$	
MULTIPLE DEPEN	DENT CLA	AIM(S) (if applicable	e)	+\$280.00	\$280.00	
****	_		TOTAL OF TH	HE ABOVE CALCULATIONS =	\$1404.00	
Applicant claim	s small en	tity status. See 37	CFR 1.27. The fees in	ndicated above are reduced by ½.	\$	
nijes jen jen				SUBTOTAL =	\$1404.00	
months from the ea	130.00 for rliest prio	r furnishing the Er rity date (37 CFR	nglish translation later t 1.492(f)).	han 20 30	\$	
				TOTAL NATIONAL FEE =	\$1404.00	
an appropriate cove	ne enclose er sheet (3	d assignment (37 of CFR 3.28, 3.31)	CFR 1.21 (h)). The ass <b>\$40.00</b> per property.	ignment must be accompanied by +	\$	
				TOTAL FEES ENCLOSED =	\$1404.00	
					Amount to be refunded:	\$
					charged:	\$
		nount of \$ <u>1404</u>		over the above fees is enclosed.		•
Please charge my Deposit Account No in the amount of \$ to cover the above fees.  A duplicate copy of this sheet is enclosed.						
The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>06-0916.</u> A duplicate copy of this sheet is enclosed.						
Fees are to be charged to a credit card. <b>WARNING:</b> Information on this form may become public. <b>Credit card</b> information should not be included on this form. Provide credit card information and authorization on PTO-2038.						
TE: Where an ap	opropriate anted to re	time limit under 3 estore the applicat	7 CFR 1.494 or 1.495 lion to pending status.	has not been met, a petition to revi-	ve (37 CFR 1.137	7 (a) or (b))
ID ALL CORRESPONDENCE TO:					<u> </u>	
legan, Henderson, Farabow, Garrett & Dunner, L.L.P.  ) I Street, N.W. hington, D.C. 20005-3315						
unigion, D.C.	ZUUUD-3.	313		rnest F. Chapman / 25,961 // IAME/REGISTRATION NO.		
ED: December						

10/019447 JC13 Rec'd PCT/PTO 3 1 DEC 2001

PATENT Customer No. 22,852 Attorney Docket No. 05788.0199

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:	)
Monika BAUER et al.	) Group Art Unit: Not Yet Assigned
Serial No.: Unassigned	) Examiner: Not Yet Assigned
PCT Filed: July 3, 2000	)
U.S. National Stage Filed: December 31, 2001	) )
For: WAVEGUIDE SYSTEMS OR STRUCTURES OR PARTS THEREOF, CONTAINING POLYCYANATE COPOLYMERS PREPARED FROM POLYFUNCTIONAL CYANATES AND FLUORINATED MONOCYANATES	<b>,</b>

# National Phase Filing of International Application No. PCT/EP00/06203

Box PCT Assistant Commissioner for Patents Washington, DC 20231

Sir:

## PRELIMINARY AMENDMENT

Prior to the examination of the above application, please amend this application as follows:

## **IN THE SPECIFICATION:**

Please amend the specification as follows:

FINNEGAN HENDERSON FARABOW GARRETT& DUNNER LLP

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com

FINNEGAN HENDERSON FARABOW GARRETT& DUNNER LLP

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com Page 1, after the title, please insert the following new headings and subheading and new paragraph:

## --Cross Reference to Related Applications

This application is a national stage filing of International Application No. PCT/EP00/06203, filed July 3, 2000, which published in the English language and claims priority of European Patent Application No. 99112596.4, filed on July 1, 1999.

## **BACKGROUND OF THE INVENTION**

Field of the Invention --.

Page 1, before line 37, add the following new subheading:

-- Description of the Related Art--.

Page 3, before line 16, add the following new section heading:

--SUMMARY OF THE INVENTION--.

Page 3, before line 31, add the following new section heading:

--DETAILED DESCRIPTION OF THE INVENTION --.

#### IN THE CLAIMS:

Please cancel now pending claims 1-16 without prejudice or disclaimer and substitute new claims 17-29 therefor as follows:

## **WHAT IS CLAIMED IS:**

17. (New) An optical waveguide system or a structure or part thereof, comprising a resin composed of at least one polycyanate copolymer, obtainable by copolymerization of at least

one difunctional cyanate of formula II:

$$N = C - O$$

$$R^{1}$$

$$R^{3}$$

$$R^{7}$$

$$R^{5}$$

$$O - C = N$$

$$R^{2}$$

$$R^{4}$$

$$R^{8}$$

$$R^{6}$$

$$(II)$$

wherein  $R^1$  to  $R^4$  and  $R^5$  to  $R^8$  are independently from each other hydrogen, optionally substituted  $C_1$ - $C_{10}$  alkyl,  $C_3$ - $C_8$ -cycloalkyl,  $C_1$ - $C_{10}$ -alkoxy, halogen, phenyl or phenoxy, the alkyl or aryl groups being unfluorinated, partly fluorinated or fully fluorinated, Z is a chemical bond,  $SO_2$ ,  $CF_2$   $CH_2$ , CHF,  $CH(CH_3)$ , isopropylene, hexafluoroisopropylene, n- or iso- $C_1$ - $C_{10}$  alkylene, O,  $NR^9$ , N=N, CH=CH, C(O)O, CH=N, CH=N-N=CH, alkylene having 1 to 8 carbon atoms, S, Si( $CH_3$ )<sub>2</sub>, and  $R^9$  is hydrogen or  $C_1$ - $C_{10}$  alkylene

with at least one monocyanate of the following formula I:

$$N \equiv C - O - R \tag{I}$$

wherein R is a straight or branched non-aromatic hydrocarbon radical or a non-aromatic hydrocarbon radical comprising a cyclic structure, the radical having the formula C(R')<sub>2</sub>-CFR"<sub>2</sub> wherein each R' is, independently from the other, hydrogen or fluorine or an

FINNEGAN HENDERSON FARABOW GARRETT & DUNNER LLP

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com

HENDERSON FARABOW GARRETT& DUNNER LLP

FINNEGAN

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com optionally substituted alkyl or alkenyl group, and each of R" may independently be defined as R' or may have an arylic structure.

- 18. (New) An optical waveguide system or a structure or part thereof according to claim 17, wherein the substituted alkyl or alkenyl group of R' is fluorinated.
- 19. (New) An optical waveguide system or a structure or part thereof according to claim 17, wherein the polycyanate copolymer is obtainable by copolymerization of at least one diffunctional cyanate of formula II, at least one monofunctional cyanate of formula I and at least one dicyanate having formula III:

$$N \equiv C - O - R^{10} - O - C \equiv N \tag{III}$$

wherein R<sup>10</sup> is a non-aromatic hydrocarbon group carrying at least one fluorine atom.

- 20. (New) An optical waveguide system or a structure or part thereof according to claim 19, wherein R<sup>10</sup> of formula III is a partly or fully fluorinated alkylene group having 1 to 15 carbon atoms.
- 21. (New) An optical waveguide system or a structure or part thereof according to claim 20, wherein the partly or fully fluorinated alkylene group has 3 to 12 carbon atoms.
- 22. (New) An optical waveguide system or a structure or part thereof according to claim 19, wherein the polycyanate copolymer is obtainable by copolymerization of at least one diffunctional cyanate of formula II, at least one monofunctional cyanate of formula I, optionally at least one dicyanate having formula III, and a monocyanate of formula IV

$$N \equiv C - O - R^1 - R^2$$

$$R^5 - R^4$$

(IV)

wherein  $R^1$  to  $R^5$  are defined as in formula II.

- 23. (New) An optical waveguide system or a structure or part thereof according to claim 19, wherein the polycyanate copolymer is obtainable by copolymerization of at least one diffunctional cyanate of formula II, at least one monofunctional cyanate of formula I, and at least one brominated monocyanate of formulas I to III, as defined above with the proviso that the monocyanates of formula I may be free of fluorine.
- 24. (New) An optical waveguide system or a structure or part thereof according to claim 23, wherein the at least one brominated monocyanate is of formula I as defined above with the proviso that the monocyanates of formula I may be free of fluorine.
- 25. (New) An optical waveguide system or a structure or part thereof according to claim 17, wherein the monocyanate of formula I is used in an amount of at least 10% by mol per mol of the polycyanate copolymer.
- 26. (New) An optical waveguide system or a structure or part thereof according to claim 17, wherein the monocyanate of formula I is used in an amount of at least 20% by mol per mol of the polycyanate copolymer.
- 27. (New) An optical waveguide or a structure or part thereof according to claim 17, wherein the polycyanate copolymer has a glass transition temperature of from 100°C to 300°C or a refractive index of about 1.35 to about 1.60 at 1.55µm or a glass transition

FINNEGAN HENDERSON FARABOW GARRETT & DUNNER LLP

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com temperature of from 100°C to 300°C and a refractive index of about 1.35 to about 1.60 at 1.55µm.

- 28. (New) An optical waveguide system or a structure or part thereof according to any one of claims 17 to 27, wherein the system, structure or part thereof is an optical fibre, a waveguide, a buffer layer, a cladding or a support for any of said structures.
- 29. (New) An optical waveguide system comprising a waveguide consisting of a resin as defined in any one of claims 17 to 27, and a buffer or cladding consisting of a resin as defined in any one of claims 17 to 27, but different from the resin of the waveguide, wherein the resin of the waveguide has a greater refractive index than that of the buffer or cladding.

#### **REMARKS**

In this Preliminary Amendment, the claims have been amended to conform them to U.S. practice and to eliminate improper multiple claim dependency.

Claims 17-29 are pending in this application. No new matter has been added.

If there is any fee due in connection with the filing of this Preliminary Amendment, please charge the fee to our Deposit Account No. 06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.

Dated: December 31, 2001

Ernest F. Chapman

Reg. No. 25,961

FINNEGAN HENDERSON FARABOW GARRETT& DUNNER LLP

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com By:



#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



## 

(43) International Publication Date 11 January 2001 (11.01.2001)

PC<sub>1</sub>

## (10) International Publication Number WO 01/02464 A1

(51) International Patent Classification<sup>7</sup>: G02B 1/04

\_\_\_\_

- (21) International Application Number: PCT/EP00/06203
- (22) International Filing Date:

3 July 2000 (03.07.2000)

(25) Filing Language:

English

C08G 73/06,

(26) Publication Language:

English

(30) Priority Data: 99112596.4

1 July 1999 (01.07.1999) EP

- (71) Applicant (for all designated States except US): PIRELLI CAVI E SISTEMI S.P.A. [IT/IT]; Viale Sarca, 222, 1-20126 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BAUER, Monika [DE/DE]; Wendenstrasse 40, D-15754 Senzig (DE). BAUER, Jörg [DE/DE]; Wendenstrasse 40, D-15754 Senzig (DE). DREYER, Christian [DE/DE]; Hauptstrasse 53a, D-55758 Niederwörresbach (DE). KEIL, Norbert [DE/DE]; Nieplitzsteig 11a, D-14089 Berlin (DE). ZAWADZKI, Crispin [DE/DE]; Pechsteinstrasse 80, D-12309 Berlin (DE).

- (74) Common Representative: PIRELLI CAVI E SISTEMI S.P.A.; Viale Sarca, 222, I-20126 Milano (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WAVEGUIDE SYSTEMS OR STRUCTURES OR PARTS THEREOF, CONTAINING POLYCYANATE COPOLY-MERS PREPARED FROM POLYFUNCTIONAL CYANATES AND FLUORINATED MONOCYANATES

VO UI/UZ404 AI

(57) Abstract: The present invention is directed to wave guide systems or structures or parts thereof, characterized in that they consist of or comprise a resin composed of at least one polycyanate copolymer, obtainable by copolymerization of at least one specific difunctional cyanate with at least one monocyanate of the formula  $N\equiv C-O-R$ , wherein R is a straight or branched non-aromatic hydrocarbon radical or a non-aromatic hydrocarbon radical comprising a cyclic structure, the radical having the formula  $C(R')_2-CFR''_2$  wherein each R' is, independently from the other, hydrogen or fluorine or an optionally substituted, preferably fluorinated alkyl or alkenyl group, and each of R'' may independently be defined as R' or may have an arylic structure. The at least one difunctional cyanate is selected from aromatic dicyanates having two arylic rings, connected with each other by a group Z wherein Z is a chemical bond,  $SO_2$ ,  $CF_2$   $CH_2$ , CHF,  $CH(CH_3)$ , isopropylene, hexafluoroisopropylene, n- or iso- $C_1-C_{10}$  alkylene, O,  $NR^9$ , N=N, CH=CH, C(O)O, CH=N, CH=N-N=CH, alkyl oxyalkylene having 1 to 8 carbon atoms, S,  $Si(CH_3)_2$ , and  $R^9$  is hydrogen or  $C_1-C_{10}$  alkyl. The polycyanate copolymer may further comprise an aromatic monocyanate and/or one or more of brominated cyanates. The polycyanate copolymers are advantageously selected for the preparation of optical waveguide systems or structures or parts thereof because they have low optical losses at 1,3 and 1.55µm.

30

35

Waveguide systems or structures or parts thereof, containing polycyanate copolymers prepared from polyfunctional cyanates and fluorinated monocyanates

The present invention is directed to optical elements in the field of waveguide systems or waveguide structures, e.g. arrayed wave guide components, prepared by copolymerization of specific polyfunctional cyanates and fluorinated monocyanates, as well as to the use of said copolymers for the preparation of said structures.

Organic polymers are increasingly interesting materials in the optical or microoptical field, in integrated optics or in microsystem techniques. In these fields, they may be used in optical instruments and apparatuses or parts thereof as well as in special optics as lenses, prisms, for fixation of optical systems, as support material for optical layers and as translucent coating materials for mirrors or lenses. Organic polymers may be used in optical fibres and for the preparation of waveguide structures. Their technical handling is relatively easy, and their density is lower in comparison to glass.

Specifically, if such plastics or organic polymers are to be used as a waveguide, a variety of requirements are to be met. The refractive index of the material should be variable in a range as broad as possible and should be adaptable to that of specific substrates. If used in the optical communication engineering, low absorptions of the materials are required at 1.3 and 1.55µm. The loss due to attenuation caused by volume defects (non-homogenities, microbubbles, microfissures) should be minimized. Besides specific technological requirements, e.g. preparation of layers and structurability, specific provisions for the use of organic polymers as waveguide structures in integrated optics are the thermal and thermo-mechanical stability, adapted extension coefficients and long term stability of optical properties.

Until now, polymethacrylates and polycarbonates have been mainly used for optical purposes. Both classes of polymers have an

30

35

excellent light transmittance, but their thermal and thermomechanical stability is not sufficient due to their chemical structure. Thus, polymethacrylates and polycarbonates cannot practically be used at temperatures exceeding 130°C which is due to their relatively low glass transition temperatures. In addition, both types of polymers are linear, un-crosslinked polymers. This has the adverse effect that they are partly solubilized in case multilayer-systems are prepared via the application of dissolved components, e.g. by spin-coating each layer. Consequently, the layer structures as obtained are not sufficiently delimitated and neat which, however, is an essential for the preparation of waveguide structures.

There are other high performance polymers which have glass transition temperatures of more than  $180\,^{\circ}\text{C}$ . Examples are polyarylethersulfones, polyarylsulfones, polyaryletherketones, polyimides and polyetherimides, the processing of which, however, is more difficult than that of polymethacrylates and polycarbonates. Another disadvantage of these systems is the relatively high optical loss at wave lengths of 1.3 and 1.55 $\mu$ m, relevant in communication engineering.

Polyperfluorocyclobutanes (PFCB) are a relatively new class of high performance polymers. Upon thermal curing they yield unsoluble cross-linked polymers which are characterized by high thermal stability. Waveguide layers prepared from PFCB show very low optical losses of 0.2 dB/cm at 1550 nm.

Also, polycyanurates have been used for the preparation of optical components. US patents 5 208 892 and 5 165 959 describe the preparation of polycyanate resins made of a single monomer (either fluorinated or non-fluorinated). German Offenlegungsschrift DE 44 35 992 Al describes optical elements prepared from polycyanurate resins. The resins are made by polymerization of dicyanate or polycyanate compounds, optionally in mixture with di- or polyphenols or di- or polyglycidyl compounds. Like polyperfluorocyclobutanes, polycyanurates yield unsoluble cross-linked polymers upon thermal curing, and these

ħ

30

35

10

polymers are as well characterized by high thermal stability. They are specifically useful due to their excellent adhesional force on a variety of substrates, for example silicon, silica or a variety of organic polymers. Refractive index and glass transition temperature of the cured cross-linked polymers may be varied in broad ranges, due to the easy availability of a great number of di- and mono-functional cyanate monomers which may be copolymerized with each other. Polycyanurates of the kind mentioned above are partly commercially available. Completely cured polycyanurates known in the art which consequently are stable for long terms may have optical losses of about 0.2 dB/cm at 1.3 $\mu$ m. However, the optical losses are not less than 0.5dB/cm at 1.55 $\mu$ m which is important in communication engineering technologies.

The present invention provides copolymers, obtainable by copolymerization of at least one monocyanate, derived from a partly or fully fluorinated alcohol ("fluorinated monocyanate"), and at least one specific difunctional organic cyanate. It has been found that such copolymers are specifically valuable in the preparation of optical waveguide systems or structures thereof having low optical losses at 1.3 and at 1.55  $\mu m$ .

Throughout the invention, "partly fluorinated" means that at least one fluorine atom is present in the molecule. "Fully fluorinated" means that hydrogen atoms are completely substituted by fluorine atoms. The whole molecules, or single organic radicals or groups (e.g. methyl, methylene, alkyl, aryl groups), respectively, may be fully fluorinated.

As fluorinated monocyanate, one, two, three or even more monocyanates of formula I may be used

 $N \equiv C - O - R \tag{I}$ 

wherein R is  $C(R')_2$ -CFR"<sub>2</sub>, wherein each R' is, independently from the other, hydrogen or fluorine or an optionally substituted, preferably fluorinated alkyl or alkenyl group having preferably

£ >

ું ક

25

30

10

For the preparation of the said copolymer, one, two, three or even more difunctional organic cyanates may be used. The expression "difunctional" means that two NCO groups are present in the molecule. The NCO groups are bound to organic radicals via the oxygen atom. The difunctional cyanate may be, but is not necessarily, partly or fully fluorinated. The organic structure of the difunctional cyanate or cyanates is selected under difunctional cyanates of formula II:

$$R^{1}$$
 $R^{3}$ 
 $R^{7}$ 
 $R^{5}$ 
 $R^{5}$ 
 $R^{6}$ 
 $R^{6}$ 
 $R^{6}$ 

(II)

wherein  $R^1$  to  $R^4$  and  $R^5$  to  $R^8$  are independently from each other hydrogen, optionally substituted  $C_1$ - $C_{10}$  alkyl,  $C_3$ - $C_8$ -cycloalkyl,  $C_1$ - $C_{10}$ -alkoxy, halogen, phenyl or phenoxy, the alkyl or aryl groups being unfluorinated, partly fluorinated or fully fluorinated, Z is a chemical bond,  $SO_2$ ,  $CF_2$   $CH_2$ , CHF,  $CH(CH_3)$ , isopropylene, hexafluoroisopropylene, n- or iso- $C_1$ - $C_{10}$  alkylene

5

which may be partly or fully fluorinated, O,  $NR^9$  with  $R^9$  being hydrogen or  $C_1$ - $C_{10}$  alkyl, N=N, CH=CH, C(O)O, CH=N, CH=N-N=CH, alkyloxyalkylene having 1 to 8 carbon atoms which is optionally partly or fully fluorinated, S, or Si(CH<sub>3</sub>)<sub>2</sub>. Examples are

2,2'-bis(4-cyanato-phenyl)propane,

2,2'-bis(4-cyanato-phenyl)hexafluoropropane,

biphenylene-4,4'dicyanate,

2,3,5,6,2',3',5',6'octafluorobiphenylene-4,4'-dicyanate.

In one embodiment of the invention, dicyanates according to formula III:

$$N = C - O - R^{10} - O - C = N \tag{III}$$

wherein R<sup>10</sup> is an organic non-aromatic hydrocarbon group carrying at least 1 fluorine atom are copolymerized into the polycyanate copolymer useful in the present invention. In formula (III), R<sup>10</sup> is preferably an alkylene group, more preferably having 3 to 12 carbon atoms. Each of the carbon atoms may carry 0, 1 or 2 or, in the case of a terminal group, 3 fluorine atoms. The carbon chain may be straight or branched or may be cyclic or may contain a cyclic part. Further, it may contain one or more C=C double bonds. In one embodiment, R<sup>10</sup> is fully fluorinated. Examples are -CH<sub>2</sub>-CF<sub>2</sub>-CF<sub>2</sub>-CH<sub>2</sub>- or -CH<sub>2</sub>-CF<sub>2</sub>-CF<sub>2</sub>-CF<sub>2</sub>-CF<sub>2</sub>-CH<sub>2</sub>.

In another embodyment of the present invention, at least one additional monocyanate having formula IV:

$$N \equiv C - O \longrightarrow R^1 - R^2$$

$$R^5 - R^4$$

(IV)

wherein R<sup>1</sup> to R<sup>5</sup> are as previously defined for formula II, is copolymerized in addition to the starting cyanates as defined above (with or without (a) cyanate(s) of formula III) in order to obtain the polycyanate copolymer. Examples for compounds of formula IV are phenylcyanate and perfluorophenylcyanate.

10

Specifically, the refractive index and the glass transition temperature may be influenced by this additive as desired.

The polycyanate copolymers according to the invention may be obtained by mixing at least one of the monocyanates of formula I, optionally in addition to at least one of formula IV, and at least one diffunctional organic cyanate of formula II, optionally in addition to at least one of formula III. The ratio of monocyanates to dicyanates may be freely chosen, provided that at least 1% by mol, preferably at least to 5% by mol, more preferably at least 10% by mol of monocyanate of structure I is present per mol of monomers to be polymerized. Preferably, the monofunctional cyanates of formulas I and IV are present in a molar amount of not more than 75% related to the total amount of moles of monomers present in the mixture to be copolymerized.

The starting monocyanate and dicyanate compounds as described above are preferably warmed up after mixing. The temperature may be chosen as required; a range of about 120°C to 170°C is preferred. Preferably, the reaction is performed in the absence of oxygen, e.g. in a sealed and preferably (under an inert gas atmosphere). The mixture is allowed to react until a liquid or viscous prepolymer (resin) is obtained. This prepolymer or resin is soluble in useful solvents, preferably in solvents having high polarity, e.g. ethylethoxyacetate or chlorobenzene. In general, the prepolymer is processed in a respective solution, e.g. by spin-coating of a solution containing 25 to 65% by weight of the prepolymer, more preferably about 50% by weight of the prepolymer. The prepolymer solution may be applied to a suitable substrate, consisting of e.g. silicon, quartz or an organic polymer. After being brought into the desired shape (e.g. a layer of desired thickness) it is cured (e.g. at temperatures in the range of 200° to 260°C) in order to provide the desired network between the cyanate groups.

If an optical wave guide system comprising a variety of different layers of the present polycyanate copolymers shall be

35

10

prepared, each different layer is applied and is cured, e.g. thermically cured, before the next layer is applied.

It shall be clear that the term "resin" is independent of the condition of the polymer, e.g. whether it is in a prepolymerized condition or is partly or completely cured.

The polycyanate copolymers according to the present invention have a glass transition temperature in the range of 100° to 300°C, and their refractive index at 1.55µm may be controlled in the desired range, specifically of from 1.35 to 1.60. Specifically, the more fluorinated monomers are used, or the more fluorine parts per weight are present in the mixture, related to the weight of the mixture to be polymerized, the lower is the refractive index of the polycyanate copolymer obtained.

On the other hand, use of brominated derivatives of the cyanate monomers as defined above will raise the refractive index of the copolymer obtained. Thus, monocyanate compounds of e.g. formula IV wherein at least one of R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup>, R<sup>4</sup> o4 R<sup>5</sup> is substituted by bromine, may be advantageously added to the mixture. In general, the more bromine is included in the polymer, the higher is the refractive index obtained. Accordingly, any of the cyanates of formulas I to IV as defined above (with the proviso that those of formula I may be free of fluorine) carrying one or more bromine atoms may be selected. However, brominated monocyanates are preferably used, either alone or in mixture with brominated polycyanates.

The polycyanate copolymers according to the present invention are used for the preparation of optical wave guide systems or parts thereof. For example, they may be used for the preparation of waveguides and waveguide structures. For such structures, use of at least two different polycyanate copolymers is preferred, wherein a polycyanate copolymer having a lower refractive index may be used for buffer and/or cladding while a polycyanate copolymer differing from the first one and having a greater

refractive index may be used as the optical waveguide. At least one of these polycyanate copolymers should have been obtained according to the present invention. The selection will be easily made by a skilled person who is able to control the refractive index via the teachings given in this application. The layers show excellent adhesion to each other and to the substrate. Waveguide structures as described above may be prepared by known methods, e.g. RIE (Reactive Ion Etching).

10

The invention is now further illustrated by way of examples.

#### Example 1

12.9 g of a substituted dicyanate of Bisphenol A (compound II wherein  $R^1\text{-}R^4$  is H,  $R^5\text{-}R^8$  is H, Z is hexafluoroisopropyl) and 3.7 g of a partly fluorinated monocyanate (compound I wherein R is  $CH_2\text{-}CF_2\text{-}CF_2\text{-}CF_3$ ) are heated to  $160^\circ C$  in a sealed vessel for a time of about four hours. The reaction is terminated before gelling starts, and a clear, pale yellow prepolymer is obtained which is viscous at  $160^\circ C$  and is solid at room temperature. The prepolymer is brought into solution by mixing it with 50 % by weight of ethylethoxyacetate (EEA). Spin-coating of this solution onto a substrate made of silicon wafer yields a layer which may be cured at  $240^\circ C$  for one hour in a drying oven. The product has a refractive index of 1.4776 at 1.55 µm.

#### Example 2

12.9 g of a substituted dicyanate of Bisphenol A (compound II wherein  $R^1-R^4$  is H,  $R^5-R^8$  is H, Z is hexafluoroisopropyl), 3.7 g of a partly fluorinated monocyanate (compound I wherein R is  $CH_2-CF_2-CF_2-CF_3$ ), and 1.3 g of a monocyanate (compound IV wherein  $R^1$ ,  $R^2$ ,  $R^4$ ,  $R^5$  are hydrogen and  $R^3$  is bromine) are heated to  $160^{\circ}C$  in a sealed vessel for a time of about four hours. The reaction is terminated before gelling starts, and a clear, pale yellow prepolymer is obtained which is viscous at  $160^{\circ}C$  and is solid at room temperature. The prepolymer is brought into solution by mixing it with 50 % by weight of EEA. Spin-coating of this solution onto a substrate made of silicon wafer yields a layer which may be cured at  $240^{\circ}C$  for one hour in a drying oven. The product has a refractive index of 1.4870 at 1.55 µm.

25

10

10

#### Example 3

9.7 g of dicyanate of Bisphenol A (compound II wherein  $R^1-R^4$  is H,  $R^5-R^8$  is H, Z is isopropyl) and 2.5 g of a fully fluorinated monocyanate (compound I wherein R is  $C-(CF_3)_2$ ) are heated to 140°C in a sealed vessel for a time of about four hours. The reaction is terminated before gelling starts, and a clear, pale yellow prepolymer is obtained which is viscous at 140°C and is solid at room temperature. The prepolymer is brought into solution by mixing it with 50 % by weight of EEA. Spin-coating of this solution onto a substrate made of silicon wafer yields a layer which may be cured at 240°C for one hour in a drying oven. The product has a refractive index of 1.5596 at 1.55  $\mu m$ .

#### Example 4

9.7 g of a substituted dicyanate of Bisphenol A (compound II wherein  $R^1-R^4$  is H,  $R^5-R^8$  is H, Z is hexafluoroisopropyl), 10.3 g of a partly fluorinated dicyanate (compound III wherein  $R^{10}$  is  $CH_2-CF_2-CF_2-CF_2-CF_2-CH_2$ ) and 1.1 g of a partly fluorinated monocyanate (compound I wherein R is  $CH_2-CF_2-CF_2-CF_3$ ) are heated to 140°C in a sealed vessel for a time of about four hours. The reaction is terminated before gelling starts, and a clear, pale yellow prepolymer is obtained which is viscous at 140°C and is solid at room temperature. The prepolymer is brought into solution by mixing it with 50 % by weight of EEA. Spin-coating of this solution onto a substrate made of silicon wafer yields a layer which is cured at 240°C for one hour in a drying oven. The product has a refractive index of 1.3689 at 1.55  $\mu$ m.

11

#### Example 5

A 50 weight-% solution of the prepolymer of example 1 in EEA is spin-coated onto a silicon wafer, yielding a layer of about 8 µm thickness. Curing is performed at 240°C in a drying oven for one hour. Onto this layer, a 50 weight-% solution of the prepolymer of example 2 in EEA is spin-coated, again yielding a layer of about 8 µm thickness. Also, this layer is cured at 240°C in the drying oven for about 1 hour. According to known methods, an aluminum layer of about 100 nm is sputtered onto the said second prepolymer layer followed by its structurization by way of photolithography and chemical etching. Subsequently, the waveguides are structured by aid of oxygen RIE techniques (typical rate 100 nm/min using pure oxygen), and the etching mask is removed by treatment in a chemical etching bath. Then, the upper cladding layer is applied by spin-coating a prepolymer solution of example 1 followed by curing at 240°C for 1 hour. Using near field technique a difference of 0.0094 of the refractive index between the waveguide and its surrounding is measured. Cut-back measurements of light intensities of wavequides of different lenght yielded a loss of 0.35 dB/cm at 1.55 µm.

\* \* \*

25

30

5

#### Claims:

 Optical waveguide system or a structure or part thereof, comprising a resin composed of at least one polycyanate copolymer, obtainable by copolymerization of at least

one difunctional cyanate of formula II:

$$N \equiv C - O \longrightarrow_{R^2}^{R^3} \xrightarrow{R^7} = R^5 \longrightarrow_{R^6}^{R^5} O - C \equiv N$$

(II)

wherein  $R^1$  to  $R^4$  and  $R^5$  to  $R^8$  are independently from each other hydrogen, optionally substituted  $C_1$ - $C_{10}$  alkyl,  $C_3$ - $C_8$ -cycloalkyl,  $C_1$ - $C_{10}$ -alkoxy, halogen, phenyl or phenoxy, the alkyl or aryl groups being unfluorinated, partly fluorinated or fully fluorinated, Z is a chemical bond,  $SO_2$ ,  $CF_2$   $CH_2$ , CHF,  $CH(CH_3)$ , isopropylene, hexafluoroisopropylene, n- or iso- $C_1$ - $C_{10}$  alkylene, O,  $NR^9$ , N=N, CH=CH, C(O)O, CH=N, CH=N-N=CH, alkyl oxyalkylene having 1 to 8 carbon atoms, S,  $Si(CH_3)_2$ , and  $R^9$  is hydrogen or  $C_1$ - $C_{10}$  alkyl

with at least one monocyanate of the following formula I:

$$N=C-O-R$$
 (I)

wherein R is a straight or branched non-aromatic hydrocarbon radical or a non-aromatic hydrocarbon radical comprising a cyclic structure, the radical having the formula  $C(R')_2-CFR''_2$  wherein each R' is, independently from the other, hydrogen or fluorine or an optionally substituted, preferably fluorinated

25

5

10

alkyl or alkenyl group, and each of R" may independently be defined as R' or may have an arylic structure.

2. Optical waveguide system or a structure or part thereof according to claim 1, characterized in that the said polycyanate copolymer is obtainable by copolymerization of at least one difunctional cyanate of formula II, at least one monofunctional cyanat of formula I and at least one dicyanate having formula III:

$$N \equiv C - O - R^{10} - O - C \equiv N \tag{III}$$

wherein  $R^{10}$  is a non-aromatic hydrocarbon group carrying at least one fluorine atom.

- 3. Optical waveguide system or a structure or part thereof according to claim 2, characterized in that R<sup>10</sup> of formula III is a partly or fully fluorinated alkylene group having 1 to 15, more preferably 3 to 12 carbon atoms.
- 4. Optical waveguides system or a structure or part thereof according to any of the preceding claims, characterized in that the said polycyanate copolymer is obtainable by copolymerization of at least one diffunctional cyanate of formula II, at least one monofunctional cyanate of formula I, optionally at least one dicyanate having formula III, and a monocyanate of formula IV

$$N \equiv C - O \longrightarrow R^{1} \qquad R^{2}$$

$$R^{5} \qquad R^{4} \qquad (IV)$$

wherein R1 to R5 are defined as in formula II.

5

10

- 5. Optical waveguide system or a structure or part thereof according to any of the preceding claims, characterized in that the said polycyanate copolymer is obtainable by copolymerization of at least one difunctional cyanate of formula II, at least one monofunctional cyanat of formula I, and at least one brominated monocyanate of formulas I to III, preferably of formula I, as defined above with the proviso that the monocyanates of formula I may be free of fluorine.
- 6. Optical waveguide system or a structure or part thereof according to any of the preceding claims, characterized in that the monocyanate of formula I as defined in claim 1 is used in an amount of at least 10%, preferably of at least 20% by mol per mol of the polycyanate copolymer.
- 7. Optical waveguide or a structure or part thereof according to any of the preceding claims, characterized in that the polycyanate copolymer has a glass transition temperature of from 100°C to 300°C and/or has a refractive index of about 1.35 to about 1.60 at 1.55µm.
- 8. Optical waveguide system or a structure or part thereof according to any of the preceding claims, characterized in that it is an optical fibre, a waveguide, a buffer layer, a cladding or a support for any of the said structures.
- 9. Optical waveguide system comprising a waveguide consisting of a resin composed as defined in any of claims 1 to 7, and a buffer and/or cladding consisting of a resin composed of a resin as defined in any of claims 1 to 7, but different from that of the waveguide, wherein the resin of the waveguide has a greater refractive index than that of the buffer and/or cladding.
- 30 10. Use of a polycyanate copolymer, obtainable by copolymerization of at least one polyfunctional cyanate selected from a difunctional cyanate of formula II:

25

30

5

 $N \equiv C - O$   $R^{1}$   $R^{3}$   $R^{7}$   $R^{5}$   $R^{5}$ 

(II)

wherein  $R^1$  to  $R^4$  and  $R^5$  to  $R^8$  are independently from each other hydrogen, optionally substituted  $C_1$ - $C_{10}$  alkyl,  $C_3$ - $C_8$ -cycloalkyl,  $C_1$ - $C_{10}$ -alkoxy, halogen, phenyl or phenoxy, the alkyl or aryl groups being unfluorinated, partly fluorinated or fully fluorinated, Z is a chemical bond,  $SO_2$ ,  $CF_2$   $CH_2$ , CHF,  $CH(CH_3)$ , isopropylene, hexafluoroisopropylene, n- or iso- $C_1$ - $C_{10}$  alkylene, O,  $NR^9$ , N=N, CH=CH, C(O)O, CH=N, CH=N-N=CH, alkyl oxyalkylene having 1 to 8 carbon atoms, S,  $Si(CH_3)_2$ , and  $R^9$  is hydrogen or  $C_1$ - $C_{10}$  alkyl

with at least one monocyanate of the following formula I:

N = C - O - R (I)

wherein R is a straight or branched non-aromatic hydrocarbon radical or a non-aromatic hydrocarbon radical comprising a cyclic structure, the radical having the formula  $C(R')_2$ -CFR"<sub>2</sub> wherein each R' is, independently from the other, hydrogen or fluorine or an optionally substituted, preferably fluorinated alkyl or alkenyl group, and each of R" may independently be defined as R' or may have an arylic structure, as a material in optical waveguide systems or structures or parts thereof, preferably of optical fibres, waveguides, buffers, claddings, or supports for such structures.

11. Use of a polycyanate copolymer according to claim 10, characterized in that the said polycyanate copolymer is obtainable by copolymerization of at least one diffunctional cyanate of formula II, at least one monofunctional cyanat of formula I and at least one dicyanate having formula III:

20

5

10

$$N \equiv C - O - R^{10} - O - C \equiv N \tag{III}$$

wherein  $R^{10}$  is a non-aromatic hydrocarbon group carrying at least one fluorine atom, preferably a partly or fully fluorinated alkylene group having 1 to 15, more preferably 3 to 12 carbon atoms.

12. Use of a polycyanate copolymer according to claim 10 or 11, characterized in that the said polycyanate copolymer is obtainable by copolymerization of at least one diffunctional cyanate of formula II, at least one monofunctional cyanate of formula I, optionally at least one dicyanate having formula III, and a monocyanate of formula IV

$$N \equiv C - O \longrightarrow_{\mathbb{R}^5} \mathbb{R}^2$$

(IV)

wherein R1 to R5 are defined as in formula II.

- 13. Use of a polycyanate copolymer according to any of claims 10 to 12 10, characterized in that the said polycyanate copolymer is obtainable by copolymerization of at least one difunctional cyanate of formula II, at least one monofunctional cyanat of formula I, and at least one brominated monocyanate of formulas I to III, preferably of formula I, as defined above with the proviso that the monocyanates of formula I may be free of fluorine.
- 25 14. Use of a polycyanate copolymer according to any of claims 10 to 13, characterized in that the monocyanate of formula I as defined in claim 1 is used in an amount of at least 10%, preferably of at least 20% by mol per mol of the polycyanate copolymer.

- 15. Use of a polycyanate copolymer according to any of claims 10 to 14, characterized in that the said polycyanate copolymer has a glass transition temperature of from 100°C to 300°C and/or has a refractive index of about 1.35 to about 1.60 at 1.55µm.
- 16. Use of a polycyanate copolymer according to any of claims 10 to 15, wherein at least the materials used for the optical waveguide and for the buffer/and or cladding are those as defined in claim 10 and the material for the waveguide has a grater refractive index than that of the buffer and/or cladding.

\* \* \*



#### **DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

WAVEGUIDE SYSTEMS OR STRUCTURES OR PARTS THEREOF, CONTAINING POLYCYANATE COPOLYMERS PREPARED FROM POLYFUNCTIONAL CYANATES AND FLUORINATED MONOCYANATES

the specification of which
is attached and/or
X was filed on December 31, 2001 as United States Application Serial No.10/019, 447 and was amended on
December 31, 2001 or
X PCT International Application No. PCT/EP00/06203, filed on, July 2, 2000

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate or § 365(a) of any PCT international application(s) designating at least one country other than the United States, listed below and have also identified below, any foreign application(s) for patent or inventor's certificate, or any PCT International application(s) having a filing date before that of the application(s) of which priority is claimed:

Country	Application Number	Date of Filing	Priority Claimed Under 35 U.S.C. 119
-Europe	99112596.4	July 1, 1999	X YES NO
			☐ YES☐ NO
🕆 i nereby claim the ben	efit under 35 U.S.C. & 119(e) of a	ny United States provisions	al application(s) listed below:
	efit under 35 U.S.C. § 119(e) of au pplication Number	ny United States provisiona	al application(s) listed below:  Date of Filing
<u> </u>		ny United States provisiona	al application(s) listed below:  Date of Filing

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) or § 365(c) of any PCT International application(s) designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of 35 U.S.C. § 12, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application(s) and the national or PCT International filing date of this application:

Application Number	Date of Filing	Status (Patented, Pending, Abandoned)		

I hereby appoint the following attorney and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P., CUSTOMER NUMBER 22,852. Douglas B. Henderson, Reg. No. 20,291; Ford F. Farabow, Jr., Reg. No. 20,630; Arthur S. Garrett, Reg. No. 20,338; Donald R. Dunner, Reg. No. 19,073; Brian G. Brunsvold, Reg. No. 22,593; Tipton D. Jennings, IV, Reg. No. 20,645; Jerry D. Voight, Reg. No. 23,020; Laurence R. Hefter, Reg. No. 20,827; Kenneth E. Payne, Reg. No. 23,098; Herbert H. Mintz, Reg. No. 26,691; C. Larry O'Rourke, Reg. No. 26,014; Albert J. Santorelli, Reg. No. 22,610; Michael C. Elmer, Reg. No. 25,857; Richard H. Smith, Reg. No. 20,609; Stephen L. Peterson, Reg. No. 26,325; John M. Romary, Reg. No. 26,331; Bruce C. Zotter, Reg. No. 27,680; Dennis P. O'Reilley, Reg. No. 27,932; Allen M. Sokal, Reg. No. 26,695; Robert D. Bajefsky, Reg. No. 25,387; Richard L. Stroup, Reg. No. 28,478; David W. Hill, Reg. No. 28,220; Thomas L. Irving, Reg. No. 28,619; Charles E. Lipsey, Reg. No. 28,165; Thomas W. Winland, Reg. No. 27,605; Basil J. Lewris, Reg. No. 28,818; Martin I. Fuchs, Reg. No. 28,508; E. Robert Yoches, Reg. No. 30,120; Barry W. Graham, Reg. No. 29,924; Susan Haberman Griffen, Reg. No. 30,907; Richard B. Racine, Reg. No. 30,415; Thomas H. Jenkins, Reg. No. 30,857; Robert E. Converse, Jr., Reg. No. 27,432; lair X. Mullen, Jr., Reg. No. 20,348; Christopher P. Foley, Reg. No. 31,354; John C. Paul, Reg. No. 30,413; Roger D. Taylor, Reg. No. 28,992; David M. Kelly, Reg. No. 30,953; Kenneth J. Meyers, Reg. No. 25,146; Carol P. Einaudi, Reg. No. 32,220; Walter Y. Boyd, Jr., Reg. No. 31,738; Steven M. Anzalone, Reg. No. 32,095; Jean B. Fordis, Reg. No. 32,984; Barbara C. McCurdy, Reg. No. 32,120; James K. Hammond, Reg. No. 31,964; Richard V. Burgujian, Reg. No. 31,744; J. Michael Jakes, Reg. No. 32,824; Thomas W. Banks, Reg. No. 32,719; Christopher P. Isaac, Reg. No. 32,616; Bryan C. Diner, Reg. No. 32,409; M. Paul Barker, Reg. No. 32,013; Andrew Chanho Sonu, Reg. No. 33,457; David S. Forman, Reg. No. 33,694; Vincent P.

Kovalick, Reg. No. 32,867; James W. Edmondson, Reg. No. 33,871; Michael R. McGurk, Reg. No. 32,045; Joann M. Neth, Reg. No. 36,363; Gerson S. Panitch, Reg. No. 33,751; Cheri M. Taylor, Reg. No. 33,216; Charles E. Van Horn, Reg. No. 40,266; Linda A. Wadler, Reg. No. 33,218; Jeffrey A. Berkowitz, Reg. No. 36,743; Michael R. Kelly, Reg. No. 33,921; James B. Monroe, Reg. No. 33,971; Doris Johnson Hines, Reg. No. 34,629; Allen R. Jensen, Reg. No. 28,224; Lori Ann Johnson, Reg. No. 34,498; and David A. Manspeizer, Reg. No. 37,540 and
Please address all correspondence to FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P., 1300 | Street, N.W., Washington, D.C. 20005, Telephone No. (202) 408-4000.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

	Full Name of First Inventor	Inventor's Signature	Date				
~	Monika BAUER	Leonite N	March 26, 2002				
ر	Residence		Citizenship				
	Senzig, Germany DEX		Germany				
	Post Office Address						
	Wendenstrasse 40, D-15754 Senzig, Germany						
	Full Name of Second Inventor	Inventor's Signature	Date				
	Jörg BAUER	4 Km	March 26, 2002				
	Residence		Citizenship				
	Senzig, Germany DEX		Germany				
	Rost Office Address						
	Wendenstrasse 40, D-15754 Senzig, Germany						
	Full Name of Third Inventor	Inventor's Signature	Date				
	Christian DREYER	C. XM	March 26, 2002				
1	#Besidence	V /	Citizenship				
	Niederwoerresbach, Germany DEX		Germany				
	Post Office Address						
	Hauptstrasse 53a, D-55758 Niederwoerresbach, Germ	any					
i	Full Name of Fourth Inventor	Inventor's Signature	Date				
	Norbert KEIL	N. Mil	March 26, 2002				
	Residence		Citizenship				
	Berlin, Germany DEX	Germany					
	Post Office Address						
	Nieplitzsteig 11a, D-14089 Berlin, Germany						
	Full Name of Fifth Inventor	Inventor's Signature	Date				
'	Crispin ZAWADZKI	Eand	March 26, 2002				
	Residence		Citizenship				
	Berlin, Germany		Germany				
	Post Office Address						
	Pechsteinstrasse 80, 12309 Berlin, Germany						